AUTO STRIPPER

DESCRIPTION AND USES

Rust-Oleum® Auto Stripper is formulated to remove all types of finish from metal surfaces of automobiles and trucks. It is fast acting and is effective on acrylics, lacquers, polyurethane and baked enamel finishes. It is non-corrosive to all common metals under normal exposure time.

This product may not be compatible with all surfaces and all conditions surrounding the application. Before applying to any surface, always test product in a small inconspicuous area to ensure no damage will result. Not recommended for use on fiberglass, plastics or any synthetic surfaces.

Carefully read all instructions on the Technical Data Sheet and cautions on the MSDS before use. Protect hands with solvent-resistant gloves and eyes with chemical splash goggles.

PRODUCTS

SKU	Description
248876	15 oz. Spray

PRODUCT APPLICATION

SURFACE PREPARATION

Remove or protect any portions of the vehicle not being stripped. Mask seams and trim openings as this will prevent bleed-back stripping of new finish.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well ventilated area such as an open garage. For best results, apply at temperatures between 65-90°F (18-32°C) and avoid direct sunlight and strong breezes.

Shake well before using. Hold can in an upright position and point arrow on top of button away from you and spray. Spray at a distance of 8-12" from the surface. Use a back and forth motion to apply a generous, even coat. Allow remover to work until the finish is blistered or softened completely. The time will vary from 20-45 minutes. Remove the paint with a flexible plastic scraper or steel wool. Flush with solvent or water to remove any residue. Allow the surface to dry before applying a new finish. Prime the metal as soon as possible to prevent flash rust. For best results, prime with a Rust-Oleum Automotive Primer and apply one of the Automotive finish coats. Recommended primers include 249319 Clean Metal Primer, 249321 Primer Sealer, 249410 Engine Primer, or one of the Stops Rust® primers.

CLEAN-UP

Clean up any spills with warm, soapy water while the Auto Stripper is still wet.

TECHNICAL DATA

RUST STRIPPER

PHYSICAL PROPERTIES

	AUTO STRIPPER
	248876 (15 oz. spray)
Composition	Methanol, Ethyl Alcohol, Methylene Chloride, and Aromatic Hydrocarbons
Volatile Organic Compounds	NA
MIR	0.4 Max
Fill Weight	15 ounces
Shelf Life	5 years
Flash Point	-156°F (-104°C)
Safety Information	For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-115
Rev.: 070814